



Millers Falls **Worker**
simply the best

PRODUCT CATALOGUE - WATER PUMPS

MAY 2021



All about pumps

TWM Millers Falls have an extensive range of pumps suitable for contractors, farmers, councils, domestic use even the hire industry.

Ideal for a range of applications including: irrigation, agriculture, firefighting and construction while some can even be used with chemicals.

Our pumps offer great value for money by combining performance and efficiency with durability and quality design, as well as availability of a full range of spare parts.

Whatever your pump needs are TWM Millers Falls have a pump that will satisfy.



PETROL - PUMPS

QWPFS6515 1.5" SINGLE IMPELLER FIREFIGHTING PUMP 6.5HP

FEATURES:

- Suction: 38mm
- Discharge port dia: 1 x 1-1/2" + 2 x 1"
- Max Head: 55m
- Max cap: 30m³/hr
- Max suction head: 8m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Engine cont output 6.5HP; 3600 speed
- Engine fuel tank: 3.6L
- Fitted with oil alert
- Packing dimensions: 47 x 38 x 40cm
- Weight: 26kg



QWPFT6515 1.5" TWIN IMPELLER FIREFIGHTING PUMP 6.5HP

FEATURES:

- Suction: 38mm
- Discharge port dia: 1 x 1-1/2" + 2 x 1"
- Max Head: 78m
- Max cap: 27m³/hr
- Max suction head: 8m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Engine cont output 6.5HP; 3600 speed
- Engine fuel tank: 3.6L
- Fitted with oil alert
- Packing dimensions: 47 x 38 x 40cm
- Weight: 26kg



QWPFT6515ES 1.5" TWIN IMPELLER FIREFIGHTING PUMP 6.5 ELEC START

FEATURES:

- Suction: 38mm
- Discharge port dia: 1 x 1-1/2" + 2 x 1"
- Max Head: 78m
- Max cap: 30m³/hr
- Max suction head: 8m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Elec & Recoil Start: Battery Included
- Engine cont output 6.5HP; 3600 speed
- Engine fuel tank: 3.6L
- Fitted with oil alert
- Packing dimensions: 47 x 38 x 40cm
- Weight: 32Kg



QWPFS652 2" SINGLE IMPELLER FIREFIGHTING PUMP 6.5HP

FEATURES:

- Suction: 50mm
- Discharge port dia: 1 x 2" + 2 x 1"
- Max Head: 65m
- Max cap: 30m³/hr
- Max suction head: 8m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Engine cont output 6.5HP; 3600 speed
- Engine fuel tank: 3.6L
- Fitted with oil alert
- Packing dimensions: 51 x 42 x 45cm
- Weight: 28kg



QWPFT652 2" TWIN IMPELLER FIREFIGHTING PUMP 6.5HP

FEATURES:

- Suction: 50mm
- Discharge port dia: 1 x 2" + 2 x 1.5"
- Max Head: 80m
- Max cap: 20m³/hr
- Max suction head: 8m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Engine cont output 6.5HP; 3600 speed
- Engine fuel tank: 3.6L
- Fitted with oil alert
- Packing dimensions: 51 x 42 x 45cm
- Weight: 29kg



PETROL - PUMPS

QWP25 1" 25MM TRANSFER PUMP

FEATURES:

- Suction: 25mm 1"
- Discharge port: 1" 25MM
- Max Head: 30m
- Max cap: 8m3/hr
- Max suction head: 7m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Engine cont output 3 HP; 3600 speed
- Engine fuel tank: 2.6L
- Fitted with oil alert
- Packing dimensions: 42 x 35 x 38cm
- Weight: 16Kg



QWP50 2" 50MM TRANSFER PUMP

FEATURES:

- Suction: 50mm
- Discharge port: 2" 50MM
- Max Head: 30m
- Max cap: 36m3/hr
- Max suction head: 7m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Engine cont output 6.5 HP; 3600 speed
- Engine fuel tank: 3.6L
- Fitted with oil alert
- Packing dimensions: 49 x 40 x 46cm
- Weight: 23Kg



QWP80 3" 80MM TRANSFER PUMP

FEATURES:

- Suction: 80mm
- Discharge port: 3" 80MM
- Max Head: 30m
- Max cap: 60m3/hr
- Max suction head: 7m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Engine cont output 7.5 HP; 3600 speed
- Engine fuel tank: 3.6L
- Fitted with oil alert
- Packing dimensions: 52 x 42 x 49cm
- Weight: 26Kg



QWP100 4" 100MM TRANSFER PUMP

FEATURES:

- Suction: 100mm
- Discharge port: 4" 100MM
- Max Head: 30m
- Max cap: 96m3/hr
- Max suction head: 7m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Engine cont output 8.0 HP; 3600 speed
- Engine fuel tank: 3.6L
- Fitted with oil alert
- Packing dimensions: 52 x 42 x 49cm
- Weight: 26Kg



QWPES106 6" WATER TRANSFER PUMP 16HP

FEATURES:

- Engine: 16 horsepower 459cc, 4 stroke, OHV, air cooled
- Electric (key) start
- Fuel capacity: 30 litres
- Suction (inlet) port: 6" (150mm)
- Outlet port: 6" (150mm)
- Pumping capacity: 150m3/hr (150000l/hr or 2500l/min)
- Self priming time: 150 seconds
- Maximum head: 25m
- Maximum suction: 8m
- Package dimensions: 72cm x 55cm x 58cm
- Package weight: 70kg





DIESEL - PUMPS

QWD50ES 2" DIESEL WATER TRANSFER PUMP ELEC START

FEATURES:

- Suction: 50mm
- Discharge port: 2" 50MM
- Max Head: 26m
- Max cap: 44m³/hr
- Max suction head: 8m
- Self priming time: <120 s
- Engine type: air-cooled, 4-stroke Diesel
- Engine cont output 5.0 HP; 3600 speed
- Electric & Recoil Start – Battery Included
- Engine fuel tank: 2.5L
- Packing dimensions: 56 x 48 x 56cm
- Weight: 38Kg



QWD80ES 3" DIESEL WATER TRANSFER PUMP ELEC START

FEATURES:

- Suction: 80mm
- Discharge port: 3" 80MM
- Max Head: 28m
- Max cap: 60m³/hr
- Max suction head: 8m
- Self priming time: <120 s
- Engine type: air-cooled, 4-stroke Diesel
- Engine cont output 6.0 HP; 3600 speed
- Electric & Recoil Start – Battery Included
- Engine fuel tank: 3.5L
- Packing dimensions: 56 x 51 x 62cm
- Weight: 51Kg



QWD100ES 4" DIESEL WATER TRANSFER PUMP ELEC START

FEATURES:

- Suction: 100mm
- Discharge port: 4" 100MM
- Max Head: 32m
- Max cap: 96m³/hr
- Max suction head: 8m
- Self priming time: <120 s
- Engine type: air-cooled, 4-stroke Diesel
- Engine cont output 10 HP; 3600 speed
- Electric & Recoil Start – Battery Included
- Engine fuel tank: 5.5L
- Packing dimensions: 67 x 53 x 65cm
- Weight: 65Kg



QWDFT62ES 2" DIESEL FIREFIGHTER PUMP ELEC START

FEATURES:

- Suction: 50mm
- Discharge port: 1 X 2" 2 X 1"
- Max Head: 80 m
- Max cap: 20m³/hr
- Max suction head: 8m
- Self priming time: <120 s
- Engine type: air-cooled, 4-stroke Diesel
- Engine cont output 6.0 HP; 3600 speed
- Electric & Recoil Start – Battery Included
- Engine fuel tank: 3.5L
- Packing dimensions: 61 x 53 x 65cm
- Weight: 47Kg



CHEMICAL - PUMP PETROL

QWCH50 2" 50MM CHEMICAL TRANSFER PUMP C/W VITON SEAL

FEATURES:

- Suction: 50mm
- Discharge port: 2" 50MM
- Max Head: 30m
- Max cap: 36m³/hr
- Max suction head: 7m
- Self priming time: 30S/4m
- Engine type: air-cooled, 4-stroke, OHV25
- Engine Petrol 7.5 HP; 3600 speed
- Engine fuel tank: 3.6L
- Fitted with oil alert
- Pump Housing: Polyester
- Mechanical Seal Material: Viton
- Packing dimensions: 54 x 41 x 43cm
- Weight: 26Kg



ELECTRIC - PUMPS

QWEH160 ELECTRIC PUMP MAX PR160-FL5.5L/MIN**

FEATURES:

- DC 12 volt
- Max pressure: 160PSI 1.1MPA
- Max flow: 5.5 L/min
- Packing dimensions: 31 x 22 x 17cm ctn
- Weight: 4kg



QWELP35 ELECTRIC PUMP MAX PR35-FLO12.5L/MI

FEATURES:

- DC 12 volt
- Max pressure: 35psi
- Max flow: 12.5 l/min
- Packing dimensions: 36 x 12 x 15cm ctn
- Weight: 3kg



QWELP40 ELECTRIC PUMP MAX PR 40-FLO17L/MIN

FEATURES:

- DC 12 volt
- Max pressure: 40PSI
- Max flow: 17L/min
- Packing dimensions: 37 x 12 x 11 cm
- Weight: 3kg

QWE75 WATER PUMP ONLY

FEATURES:

- Rated voltage: 240V
- Power: 0.75hp
- Max flow: 45 L/min
- Max head: 50m
- Inlet/outlet: 1"x1"
- Max suction: 9m
- Packing dimensions: 35 x 26 x 40cm
- Weight: 13KG



QWE7570 PRESSURE PUMP C/W CONTROL VALVE

FEATURES:

- Rated voltage: 240V
- Power: 0.75hp
- Max flow: 45 L/min
- Max head: 50m
- Inlet/outlet: 1"x1"
- Max suction: 9m
- N.W.: 13KG
- Packing dimensions: 35 x 26 x 40cm



QWEPU10 PUMP CONTROL VALVE

FEATURES:

- Rated voltage: 240V
- Max current: 10A
- Frequency: 50Hz
- Max power: 1.1 kw
- Max Working Pressure: 10 bar
- Fittings: 25.4mm 1"
- Packing dimensions: 23 x 17 x 18
- Weight: 1kg



FLEXIBLE DRIVE WATER PUMP - PETROL

QWPE55FX FLEXIBLE DRIVE WATER PUMP 3" 80MM

FEATURES:

- Engine: 5.5HP 4 stroke, OHV, air cooled
- Full Protective Swivel Roll Frame
- Impeller: Open Vane Vortex
- Discharge Outlet: 3" (80mm)
- Max Solids: 25mm
- Pumping capacity: 56m3/hr
- Drive Cable: 6 Meter
- Maximum Head: 25m
- Package dimensions: 80m x 65cm x 60cm
- Package weight: 50kg





ACCESSORIES

QWFKIT50 MM BUSH FIRE KIT

FEATURES:

- 20 metres 3/4" hose fitted with nozzle & tail fitting
- 5 metres 2" suction hose with filter & tail
- Packing dimensions: 61 x 15 x 61cm ctn
- Weight: 10Kg



QWFK60MC FIREFIGHTING CANVAS HOSE WITH BRASS FIT

FEATURES:

- 60m 3/4" firefighting canvas hose with brass fittings
- Packing dimensions: 49 x 41 x 19
- Weight : 10Kg



QWFK20M FIREFIGHTING HOSE WITH BRASS FIT

FEATURES:


- 20m 3/4" firefighting hose with brass fittings
- Packing dimensions: 49 x 41 x 19
- Weight : 10Kg



QWFKIT2 2" ADAPTOR SUIT QWFKIT

FEATURES:

- 2 piece Heavy Duty Steel Adaptor
- Enables a 1.5" diameter suction hose to be able to screwed onto a 2" inlet on the fire pump



LAYFLAT HOSE

Item Number	Description	Working Pressure (BAR)	Burst Pressure (BAR)	Length (M/ROLL)
QWLF3825	1 1/2" PVC Layflat Hose -25MTR	4	12	25
QWLF38100	1 1/2" PVC Layflat Hose -100MT	4	12	100
QWLF5025	2" PVC Layflat Hose -25MTR	4	12	25
QWLF50100	2" PVC Layflat Hose -100MTR	4	12	100
QWLF7525	3" PVC Layflat Hose -25MTR	4	12	25
QWLF75100	3" PVC Layflat Hose -100MTR	4	12	100
QWLF10025	4" PVC Layflat Hose -25MTR	4	12	25
QWLF100100	4" PVC Layflat Hose -100MTR	4	12	100



CAMLOCK KITS



Camlock C



Camlock E



Fibre Washers



Camlock A



Hose Clamps

Item Number	Description
QWCL38KIT	1.5inch Aluminium Camlock Fittings Kit Includes Camlocks A, C, E, 4x Hose Clamps & 4x Fibre Washers
QWCL50KIT	2inch Aluminium Camlock Fitting Includes Camlocks A, C, E, 4x Hose Clamps & 4x Fibre Washers
QWCL75KIT	3inch Aluminium Camlock Fitting Includes Camlocks A, C, E, 4x Hose Clamps & 4x Fibre Washers
QWCL100KIT	4inch Aluminium Camlock Fittings Kit Includes Camlocks A, C, E, 4x Hose Clamps & 4x Fibre Washers



TWM Imports Pty Ltd

5-15 James Court,
Tottenham, Victoria 3012
Phone 03 9314 8588
Email : sales@twm.com.au



www.twm.com.au

Millers Falls *Worker*
simply the best