



OUR MOST EXCITING RANGE OF GENERATORS TO DATE WITH FEATURES AND BENEFITS THAT ARE SECOND TO NONE.



TWM Imports is excited to introduce our new range of generators. The most extensive range we have ever had with features, benefits and pricing second to none in the Australian market.

Generator Features

(not included with all models)

- 12-Volt DC Circuit
- 15 AMP 240 Volt IP44 Socket
- 15 AMP 240 Volt IP66 Socket
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Sockets
- ATS Auto Transfer Switch
- AVR Automatic Voltage Regulator
- · Battery Included
- Digital Hertz Meter
- Digital Hour Usage Meter
- Digital Inverter Technology
- Digital Volt Meter
- Electric Start
- Euro V Emissions Certification
- Heavy Duty Copper Alternator
- Large Low Noise Muffler
- Lift Up Lid Silenced Diesel Generator
- Long Range 30 Litre Fuel Tank
- Long Range 40 Litre Fuel Tank
- Low Idle Mode
- Low Noise Emission
- Massive Air Cleaner
- Never Flat Wheels
- Oil Alert Light
- Overload Alarm
- Parallel Connectivity
- Push Button Start
- RCD Safety Switch Worksite Compliant
- Silenced Diesel
- Silenced Quiet Running
- Sine Wave Technology
- Telescopic Handle
- Two Wire Remote Start
- USB 5 Volt Power Supply















GSC12000iY

PURE SINE WAVE INVERTER GENERATOR

Superior Quality - Unprecedented Functionality - Exceptional Value

This is the most feature loaded Pure Sine Wave Generator available today. Digital inverter generators produce a pure sine wave, this is the same type of current supplied to homes and busineses by utility companies. Pure sine wave output is a superior and cleaner form of power when compared to modified sine wave or square wave current in traditional generators.

It is generally agreed that a pure sine wave generator is preferable when used as a home or industry power supply or a backup source especially when powering newer LED TVs, CFL lights, audio equipment, clocks and inductive loads like brushless motors found in many household appliances.

The GSC12000iY is ideal for: powering an entire house, building sites requiring a high output of pure sine wave power, Automatic Recharging of Solar Batteries via 2 Wire Remote Start or Automatic Start function when Mains Power Fails using an (optional) ATS – Auto Transfer Switch.

- 15 AMP IP44 Socket
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Socket
- ATS Auto Transfer Switch Connection
- · Battery Included
- · Digital Hour Usage, Hertz and Volt Meter
- Electric Start
- Euro V Emissions Certification
- Heavy Duty Copper Alternator
- Large Low Noise Muffler
- Long Range 34 Litre Fuel Tank
- Low Idle Mode
- Low Noise Emission
- Massive Air Cleaner
- Never Flat Wheels
- Oil Alert Light
- Overload Alarm
- Pure Sine Wave Inverter
- Push Button Start
- Two Wire Remote Start
- USB 5 Volt Power Supply



Model Number	GSC12000iY	AMPS	37.5
Volts	240	FREQ	50HZ
Engine Displacement	459cc (16HP)	THD	< 3%
Max Power kVa	11.85	POWER FACTOR	0.8
Rated Power kVa	11.25	PHASE	SINGLE
Max Power kW	9.5	RPM	3700
Rated Power kW	9.0	FUEL CAPACITY	34L
dBA	73	Run Time 50%-100% Load	13 - 7 hrs
Dimensions L x W x H / CM	82 x 60 x 63	Weight	80 KG



GST11000A Generator

FEATURE PACKED GENERATOR FOR TRADE, INDUSTRY, POWER BACKUP OR SOLAR RECHARGE

Superior Quality – Unprecedented Functionality – Exceptional Value

Fully loaded, feature packed Premium Quality Generator at an affordable price. Ideal for powering an entire house, Building Sites requiring RCD Earth Leakage and IP66 Socket Compliance and a high output of power, Automatic Recharging of Solar Batteries via 2 Wire Remote Start, Automatic Start when Mains Power Fails using an (optional) ATS – Auto Transfer Switch.

- 15 AMP 240 Volt IP66 Socket
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Socket
- · ATS Auto Transfer Switch Connection
- AVR Automatic Voltage Regulator
- · Battery Included
- · Digital Hour Usage, Hertz, and Volt Meter
- Electric Start
- Euro V Emissions Certification
- · Heavy Duty Copper Alternator
- · Long Range 30 Litre Fuel Tank
- · Low Noise Emission
- Never Flat Wheels
- Oil Alert Light
- · Push Button Start
- RCD Safety Switch Worksite Compliant
- Two Wire Remote Start



Model Number	GST11000A	AMPS	33.3
Volts	240	FREQ	50HZ
Engine Displacement	459cc (16HP)	THD	< 5%
Max Power kVa	10.6	POWER FACTOR	0.8
Rated Power kVa	10.0	PHASE	SINGLE
Max Power kW	8.5	RPM	3000
Rated Power kW	8.0	FUEL CAPACITY	30L
dBA	79	Run Time 50% Load	11 hrs
Dimensions L x W x H / CM	73 x 55 x 66	Weight	105 kg



GST11000E Generator

Superior Quality - Unprecedented Functionality - Exceptional Value

Feature packed Premium Quality Generator for Trade, Industry, Rural Applications or Power Backup ideal for powering an entire house, Building Sites requiring RCD Earth Leakage Compliance and high output of power.

- 15 AMP 240 Volt IP66 Socket
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Socket
- AVR Automatic Voltage Regulator
- · Battery Included
- · Digital Hour Usage, Hertz, and Volt Meter
- Electric Start
- · Euro V Emissions Certification
- · Heavy Duty Copper Alternator
- Long Range 30 Litre Fuel Tank
- Low Noise Emission
- Massive Air Cleaner
- · Never Flat Wheels
- Oil Alert Light
- RCD Safety Switch Worksite Compliant



Model Number	GST11000E	AMPS	33.3
Volts	240	FREQ	50HZ
Engine Displacement	459cc (16HP)	THD	< 5%
Max Power kVa	10.6	POWER FACTOR	0.8
Rated Power kVa	10.0	PHASE	SINGLE
Max Power kW	8.5	RPM	3000
Rated Power kW	8.0	FUEL CAPACITY	30L
dBA	79	Run Time 50% Load	11 hrs
Dimensions L x W x H / CM	73 x 55 x 66	Weight	105 kg



GST9500E Generator

Superior Quality – Unprecedented Functionality – Exceptional Value

Powerful, Feature Packed economical Generator perfect for a wide range of uses. Ideal for Builders, Farmers, Industry, Trade and Power Back up applications

- 2 x 15 AMP 240 Volt IP44 Sockets
- AVR Automatic Voltage Regulator
- Battery Included
- · Digital Hour Usage, Hertz and Volt Meter
- Electric Start
- · Euro V Emissions Certification
- Heavy Duty Copper Alternator
- Long Range 30 Litre Fuel Tank
- · Low Noise Emission
- Never Flat Wheels
- Oil Alert Light





Model Number	GST9500E	AMPS	27.1
Volts	240	FREQ	50HZ
Engine Displacement	420cc (14HP)	THD	< 5%
Max Power kVa	9.4	POWER FACTOR	0.8
Rated Power kVa	8.1	PHASE	SINGLE
Max Power kW	7.5	RPM	3000
Rated Power kW	6.5	FUEL CAPACITY	30L
dBA	82	Run Time 50% Load	12 hrs
Dimensions L x W x H / CM	73 x 55 x 66	Weight	100 KG



GST7000 Generator

Superior Quality – Unprecedented Functionality – Exceptional Value

Powerful, Feature Packed economical Generator perfect for a wide range of uses. Ideal for Builders, Farmers, Industry, Trade and Power Back up applications

- 2 x 15 AMP 240 Volt IP44 Sockets
- AVR Automatic Voltage Regulator
- Euro V Emissions Certification
- · Heavy Duty Copper Alternator
- Low Noise Emission
- · Oil Alert Shut Down





Model Number	GST7000	AMPS	20.8
Volts	240	FREQ	50HZ
Engine Displacement	420cc (14HP)	THD	< 5%
Max Power kVa	6.875	POWER FACTOR	0.8
Rated Power kVa	6.25	PHASE	SINGLE
Max Power kW	5.5	RPM	3000
Rated Power kW	5.0	FUEL CAPACITY	7L
dBA	89	Run Time 50% Load	3 hrs
Dimensions L x W x H / CM	76 x 56 x 55	Weight	66 KG



GST4500 Generator

Superior Quality - Unprecedented Functionality - Exceptional Value

Powerful, Feature Packed economical Generator perfect for a wide range of uses. Ideal for Builders, Farmers, Industry, Trade and Power Back up applications

- 2 x 15 AMP 240 Volt IP44 Sockets
- AVR Automatic Voltage Regulator
- Euro V Emissions Certification
- Heavy Duty Copper Alternator
- Low Noise Emission
- · Oil Alert Shut Down





Model Number	GST4500	AMPS	13.3
Volts	240	FREQ	50HZ
Engine Displacement	223cc (8HP)	THD	< 5%
Max Power kVa	4.375	POWER FACTOR	0.8
Rated Power kVa	4.0	PHASE	SINGLE
Max Power kW	3.5	RPM	3000
Rated Power kW	3.2	FUEL CAPACITY	3.6L
dBA	87	Run Time 50% Load	2.5 hrs
Dimensions L x W x H / CM	64x 47 x 45	Weight	45 KG



GST3500 Generator

Superior Quality - Unprecedented Functionality - Exceptional Value

Powerful, Feature Packed economical Generator perfect for a wide range of uses. Ideal for Builders, Farmers, Industry, Trade and Power Back up applications

- 2 x 15 AMP 240 Volt IP44 Sockets
- AVR Automatic Voltage Regulator
- Euro V Emissions Certification
- · Heavy Duty Copper Alternator
- Low Noise Emission
- · Oil Alert Shut Down





Model Number	GST3500	AMPS	10.4
Volts	240	FREQ	50HZ
Engine Displacement	196cc (6.5HP)	THD	< 5%
Max Power kVa	3.5	POWER FACTOR	0.8
Rated Power kVa	3.125	PHASE	SINGLE
Max Power kW	2.8	RPM	3000
Rated Power kW	2.5	FUEL CAPACITY	3.6L
dBA	87	Run Time 50% Load	2.5 hrs
Dimensions L x W x H / CM	65x 47 x 45	Weight	37 KG



GSC5000i-O Generator

Superior Quality - Unprecedented Functionality - Exceptional Value

Mobile Solution for Camping, Recreational Use or Power Backup. Inverter Portable Generators are the perfect solution when high output, high quality pure sine wave power is required from a silenced, user and noise friendly source.

The GSC5000i-O is powerful enough to run and entire campsite, worksite or home yet still relatively portable and extremely quiet, it also has a handy remote-control function enabling starting and stopping from anywhere within 10 meters from the unit.

Applications include: Camping, Caravanning & RVs, Home and small office, Shop and production use, Precision Instruments, Small to medium power tools, market sellers, Industry, Domestic, Light industrial, Light commercial.

Parallel Connectivity: Use the (optional) HEAVY DUTY parallel connection cable to join two of the same inverter generators together to double the output. With two GSC5000i-O units in parallel you get a massive 10kVa at peak or 8,000 peak Watts.

- Battery Included
- Digital Hour Usage, Hertz and Volt Meter
- Digital Inverter Technology
- Electric Start
- · Euro V Emissions Certification
- IP44 15AMP Socket
- Low Idle Mode
- Low Noise Emission
- Oil Alert Light
- Parallel Connectivity
- · Push Button Start
- Silenced Quiet Running
- Sine Wave Technology
- · Telescopic Handle
- USB 5 Volt Power Supply



Model Number	GSC5000i-O	AMPS	14.6
Volts	240	FREQ	50HZ
Engine Displacement	223 cc	THD	< 3%
Max Power kVa	5.0	POWER FACTOR	0.8
Rated Power kVa	4.37	PHASE	SINGLE
Max Power kW	4.0	RPM	3600
Rated Power kW	3.5	FUEL CAPACITY	10L
dBA	58	Run Time 50%-100% Load	8.5 - 5.5 HRS
Dimensions L x W x H / cm	67 x 56 x 60	Weight	52 kg



GSC3750i-Y Generator

Superior Quality - Unprecedented Functionality - Exceptional Value

Yamaha Powered Mobile Solution for Camping, Recreational Use or Power Backup. Inverter Portable Generators are the perfect solution when high output, high quality pure sine wave power is required from a silenced, user and noise friendly source.

The GSC3750i-Y is powerful enough to help run your campsite, worksite or home yet still extremely portable and ultraquiet. Add to that the reputation that comes from a genuine Yamaha engine and you have a winning combination.

Applications include; Camping, Caravanning & RVs, Home and small office, Shop and production use, Precision Instruments, Small to medium power tools, market sellers, Industry, Domestic, Light industrial, Light commercial. Parallel Connectivity; use the (optional) HEAVY DUTY parallel connection cable to join two of the same inverter generators together to double the output. With two GSC3750i-Y units in parallel you get a massive 7.5kVa at peak or 6,000 peak Watts.

- Digital Hour Usage, Hertz and Volt Meter
- Digital Inverter Technology
- Euro V Emissions Certification
- IP44 15AMP Socket
- Low Idle Mode
- Low Noise Emission
- Oil Alert Light
- Parallel Connectivity
- Silenced Quiet Running
- Sine Wave Technology
- Telescopic Handle
- **USB 5 Volt Power Supply**





Model Number	GSC3750i-Y	AMPS	11.67
Volts	240	FREQ	50HZ
Engine YAMAHA	MZ175	THD	< 3%
Max Power kVa	3.75	POWER FACTOR	0.8
Rated Power kVa	3.5	PHASE	SINGLE
Max Power kW	3.0	RPM	3600
Rated Power kW	2.8	FUEL CAPACITY	10L
dBA	60	Run Time 50%-100% Load	9.0 - 6.0 HRS
Dimensions L x W x H / CM	67 x 56 x 60	Weight	53KG



GSC2800i-O Generator

Superior Quality – Unprecedented Functionality – Exceptional Value

Mobile Solution for Camping, Recreational Use or Power Backup. Inverter Portable Generators are the perfect solution when high output, high quality pure sine wave power is required from a silenced, user and noise friendly source

The GSC2800i-O is power and economy without compromise. The generator will run your RV or Caravan Air Conditioner with ease, plus a whole range of appliances and tools. Lightweight, quiet, reliable, portable and affordable.

Applications include: Camping, Caravanning & RVs, Home and small office, Shop and production use, Precision Instruments, Small to medium power tools, market sellers, Industry, Domestic, Light industrial, Light commercial

Parallel Connectivity; use the (optional) HEAVY DUTY parallel connection cable to join two of the same inverter generators together to double the output. With two GSC2800I-O units in parallel you get a massive 5.75kVa at peak or 4,600 peak Watts.

- Digital Hour Usage, Hertz and Volt Meter
- Digital Inverter Technology
- Euro V Emissions Certification
- IP44 15AMP Socket
- · Low Idle Mode
- Low Noise Emission
- · Oil Alert Light
- Parallel Connectivity
- Silenced Quiet Running
- Sine Wave Technology
- Telescopic Handle
- USB 5 Volt Power Supply



Model Number	GSC2800i-O	AMPS	7.5
Volts	240	FREQ	50HZ
Engine Displacement	79 CC	THD	< 3%
Max Power kVa	2.875	POWER FACTOR	0.8
Rated Power kVa	2.25	PHASE	SINGLE
Max Power kW	2.3	RPM	3600-5300
Rated Power kW	1.8	FUEL CAPACITY	4L
dBA	60	Run Time 50%-100% Load	6.0 - 4.0 HRS
Dimensions L x W x H / CM	58 x 38 x 55	Weight	22KG



GSD13000Q Diesel Silenced Generator

Superior Quality - Unprecedented Functionality - Exceptional Value

Diesel Generators have a number of advantages over petrol powered units. Diesel is far safer to handle, on many worksites' petrol is not allowed due to safety concerns. Diesel fuel will store for longer periods and provides better fuel consumption figures. The GSD13000Q is powerful enough to run an entire household or worksite as well as a variety of high consumption tools, machinery, welders and the like.

The silencing enclosure of this diesel generator reduces the sound level to a moderate 70 dBA at 7 meters allowing for work and activities to continue in the near vicinity without excessive noise pollution.

The ATS and Two Wire Remote Start functions of this generator give it greater versatility as it can be easily connected to automatically recharge off grid batteries via the battery controller as well as wired direct to the house or workshop mains power via the ATS feature and optional ATS Box, meaning the generator will start automatically in case of mains power failure and stop automatically when mains power is restored.

IP66 Waterproof Outlets are supplied including a 32-amp 240V outlet and 2 x 15-amp outlets, we even supply a 32amp IP66 plug. The RCD (earth leakage safety switch) fitted to the GSD13000Q provides an extra level of safety and gives this generator a tick of approval on many construction and mining sites.

- 12-Volt DC Circuit
- 15 AMP 240 Volt IP66 Sockets x 2
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Sockets
- ATS Auto Transfer Switch
- AVR Automatic Voltage Regulator
- Battery Included
- Digital Hour Usage, Hertz and Volt Meter
- Electric Start
- Heavy Duty Copper Alternator
- Low Noise Emission
- · Oil Alert Light
- RCD Safety Switch
- Silenced Diesel
- Two Wire Remote Start





Model Number	GSD13000Q	AMPS	41.7
Volts	240	FREQ	50HZ
Engine Displacement	870cc	THD	< 8%
Max Power kVa	13.750	POWER FACTOR	0.8
Rated Power kVa	12.5	PHASE	SINGLE
Max Power kW	11.0	RPM	3000
Rated Power kW	10.0	FUEL CAPACITY	21L
dBA	70	Run Time 50%-100% Load	6.5 - 5.0 HRS
Dimensions L x W x H / CM	98 x 60 x 95	Weight	206KG



GSD13000E Diesel Open Frame Generator

Superior Quality - Unprecedented Functionality - Exceptional Value

Diesel Generators have a number of advantages over petrol powered units. Diesel is far safer to handle, on many worksites' petrol is not allowed due to safety concerns. Diesel fuel will store for longer periods and provides better fuel consumption figures. The GSD13000E is powerful enough to run an entire household or worksite as well as a variety of high consumption tools, machinery, welders and the like.

The ATS and Two Wire Remote Start functions of this generator give it greater versatility as it can be easily connected to automatically recharge off grid batteries via the battery controller as well as wired direct to the house or workshop mains power via the ATS feature and optional ATS Box, meaning the generator will start automatically in case of mains power failure and stop automatically when mains power is restored.

IP66 Waterproof Outlets are supplied including a 32-amp 240V outlet and 2 x 15-amp outlets, we even supply a 32-amp IP66 plug. The RCD (earth leakage safety switch) fitted to the GSD13000E provides an extra level of safety and gives this generator a tick of approval on many construction and mining sites.

- 12-Volt DC Circuit
- 15 AMP 240 Volt IP66 Sockets x 2
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Sockets
- ATS Auto Transfer Switch Connection
- AVR Automatic Voltage Regulator
- Battery Included
- Digital Hour Usage, Hertz and Volt Meter
- Electric Start
- Heavy Duty Copper Alternator
- Low Noise Emission
- Oil Alert Light
- RCD Safety Switch
- Two Wire Remote Start





Model Number	GSD13000E	AMPS	41.7
Volts	240	FREQ	50HZ
Engine Displacement	870cc	THD	< 8%
Max Power kVa	13.750	POWER FACTOR	0.8
Rated Power kVa	12.5	PHASE	SINGLE
Max Power kW	11.0	RPM	3000
Rated Power kW	10.0	FUEL CAPACITY	46L
dBA	82	Run Time 50%-100% Load	6.5 - 5.0 HRS
Dimensions L x W x H / CM	93 x 70 x 96	Weight	212KG



GSD9000Q Diesel Silenced Generator

Superior Quality - Unprecedented Functionality - Exceptional Value

The GSD9000Q is powerful enough to run an entire household or worksite as well as a variety of high consumption tools, machinery, welders and the like. The silencing enclosure of this diesel generator reduces the sound level to a comfortable 65 dBA at 7 meters allowing for work and activities to continue in the near vicinity without excessive noise pollution.

The ATS and Two Wire Remote Start functions of this generator give it greater versatility as it can be easily connected to automatically recharge off grid batteries via the battery controller as well as wired direct to the house or workshop mains power via the ATS feature and optional ATS Box, meaning the generator will start automatically in case of mains power failure and stop automatically when mains power is restored.

IP66 Waterproof Outlets are supplied including a 32-amp 240V outlet and a 15-amp 240V outlet, we even supply a 32amp IP66 plug. The RCD (earth leakage safety switch) fitted to the GSD9000Q provides an extra level of safety and gives this generator a tick of approval on many construction and mining sites. The unit also provides a 12v DC @ 8amp power supply handy for charging 12-volt batteries. The lift up lid on this generator gives great access to the unit for service and maintenance purposes without compromising its sound deadening qualities.

- 12-Volt DC Circuit
- 15 AMP 240 Volt IP66 Socket
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Socket
- · ATS Auto Transfer Switch
- · AVR Automatic Voltage Regulator
- · Digital Hour Usage, Hertz and Volt Meter
- Lift Up Lid Silenced Diesel Generator
- Heavy Duty Copper Alternator
- Electric Start
- Low Noise Emission
- Never Flat Wheels
- Oil Alert Light
- RCD Safety Switch
- Silenced Diesel
- Two Wire Remote Start





Model Number	GSD9000Q	AMPS	27.1
Volts	240	FREQ	50HZ
Engine Displacement	499cc	THD	< 8%
Max Power kVa	8.750	POWER FACTOR	0.8
Rated Power kVa	8.125	PHASE	SINGLE
Max Power kW	7.0	RPM	3000
Rated Power kW	6.5	FUEL CAPACITY	15L
dBA	65	Run Time 50%-100% Load	7.5 - 5.0 HRS
Dimensions L x W x H / CM	94 x 58 x 89	Weight	174KG



GSD9000E Diesel Open Frame Generator

Superior Quality – Unprecedented Functionality – Exceptional Value

The GSD9000E is powerful enough to run an entire household or worksite as well as a variety of high consumption tools, machinery, welders and the like.

The ATS and Two Wire Remote Start functions of this generator give it greater versatility as it can be easily connected to automatically recharge off grid batteries via the battery controller as well as wired direct to the house or workshop mains power via the ATS feature and optional ATS Box, meaning the generator will start automatically in case of mains power failure and stop automatically when mains power is restored.

IP66 Waterproof Outlets are supplied including a 32-amp 240V outlet and a 15-amp 240V outlet, we even supply a 32amp IP66 plug. The RCD (earth leakage safety switch) fitted to the GSD9000E provides an extra level of safety and gives this generator a tick of approval on many construction and mining sites. The unit also provides a 12v DC @ 8amp power supply handy for charging 12-volt batteries.

- 12-Volt DC Circuit
- 15 AMP 240 Volt IP66 Socket
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Socket
- · ATS Auto Transfer Switch Connection
- AVR Automatic Voltage Regulator
- · Battery Included
- · Digital Hour Usage, Hertz and Volt Meter
- Heavy Duty Copper Alternator
- Electric Start
- Low Noise Emission
- Never Flat Wheels
- Oil Alert Light
- RCD Safety Switch
- Two Wire Remote Start





Model Number	GSD9000E	AMPS	27.1
Volts	240	FREQ	50HZ
Engine Displacement	499cc	THD	< 8%
Max Power kVa	8.750	POWER FACTOR	0.8
Rated Power kVa	8.125	PHASE	SINGLE
Max Power kW	7.0	RPM	3000
Rated Power kW	6.5	FUEL CAPACITY	15L
dBA	82	Run Time 50%-100% Load	7.5 - 5.0 HRS
Dimensions L x W x H / CM	94 x 58 x 89	Weight	131KG



GSD7500Q Diesel Silenced Generator

Superior Quality – Unprecedented Functionality – Exceptional Value

The GSD7500Q is a mid-powered generator capable of running a small to mid-size property as well as a variety of tools, machinery and the like. The silencing enclosure of this diesel generator reduces the sound level to a comfortable 65 dBA at 7 meters allowing for work and activities to continue in the near vicinity without excessive noise pollution.

The ATS and Two Wire Remote Start functions of this generator give it greater versatility as it can be easily connected to automatically recharge off grid batteries via the battery controller as well as wired direct to the house or workshop mains power via the ATS feature and optional ATS Box, meaning the generator will start automatically in case of mains power failure and stop automatically when mains power is restored.

IP66 Waterproof Outlets are supplied including a 32-amp 240V outlet and a 15-amp 240V outlet, we even supply a 32amp IP66 plug. The RCD (earth leakage safety switch) fitted to the GSD7500Q provides an extra level of safety and gives this generator a tick of approval on many construction and mining sites. The unit also provides a 12v DC @ 8amp power supply handy for charging 12-volt batteries. The lift up lid on this generator gives great access to the unit for service and maintenance purposes without compromising its sound deadening qualities.

- AT12-Volt DC Circuit
- 15 AMP 240 Volt IP66 Socket
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Socket
- ATS Auto Transfer Switch
- AVR Automatic Voltage Regulator
- Digital Hour Usage, Hertz and Volt Meter
- Lift Up Lid Silenced Diesel Generator
- Heavy Duty Copper Alternator
- Electric Start
- Low Noise Emission
- Never Flat Wheels
- Oil Alert Light
- RCD Safety Switch
- Silenced Diesel
- Two Wire Remote Start



Model Number	GSD7500Q	AMPS	20.8
Volts	240	FREQ	50HZ
Engine Displacement	418cc	THD	< 8%
Max Power kVa	6.785	POWER FACTOR	0.8
Rated Power kVa	6.25	PHASE	SINGLE
Max Power kW	5.5	RPM	3000
Rated Power kW	5.0	FUEL CAPACITY	15 L
dBA	65	Run Time 50%-100% Load	9.0 - 6.5 HRS
Dimensions L x W x H / CM	94 x 58 x 89	Weight	170KG



GSD7500E Diesel Open Frame Generator

Superior Quality - Unprecedented Functionality - Exceptional Value

The GSD7500E is a mid-powered generator capable of running a small to mid-size property as well as a variety of tools, machinery and the like.

The ATS and Two Wire Remote Start functions of this generator give it greater versatility as it can be easily connected to automatically recharge off grid batteries via the battery controller as well as wired direct to the house or workshop mains power via the ATS feature and optional ATS Box, meaning the generator will start automatically in case of mains power failure and stop automatically when mains power is restored.

IP66 Waterproof Outlets are supplied including a 32-amp 240V outlet and a 15-amp 240V outlet, we even supply a 32amp IP66 plug. The RCD (earth leakage safety switch) fitted to the GSD7500E provides an extra level of safety and gives this generator a tick of approval on many construction and mining sites. The unit also provides a 12v DC @ 8amp power supply handy for charging 12-volt batteries.

- AT12-Volt DC Circuit
- 15 AMP 240 Volt IP66 Socket
- 32 AMP 240 Volt IP66 Plug Supplied
- 32 AMP 240 Volt IP66 Socket
- ATS Auto Transfer Switch Connection
- AVR Automatic Voltage Regulator
- Digital Hour Usage, Hertz and Volt Meter
- Heavy Duty Copper Alternator
- Electric Start
- Low Noise Emission
- Never Flat Wheels
- Oil Alert Light
- RCD Safety Switch
- Two Wire Remote Start



Model Number	GSD7500E	AMPS	20.8
Volts	240	FREQ	50HZ
Engine Displacement	418cc	THD	< 8%
Max Power kVa	6.785	POWER FACTOR	0.8
Rated Power kVa	6.25	PHASE	SINGLE
Max Power kW	5.5	RPM	3000
Rated Power kW	5.0	FUEL CAPACITY	18 L
dBA	82	Run Time 50%-100% Load	9.0 - 6.5 HRS
Dimensions L x W x H / CM	94 x 58 x 89	Weight	113KG



GSATS240-P - Auto Transfer Switch 240V - Suits Petrol

Superior Quality - Unprecedented Functionality - Exceptional Value

The ATS function gives our generators greater versatility, the switch can be wired direct to the house or workshop mains power fuse box. In Automatic mode the switch will automatically start the generator if mains power fails for whatever reason. Once the generator is up to full speed and generating voltage at 50Hz the switch will feed the power into the required load point. Once mains power is restored the ATS will transfer load from the generator back to mains power then shut down the generator. This same function can also be performed in manual mode if required.

THE WIRING OF THE ATS MUST ONLY BE PERFORMED BY A LICENSED ELECTRICIAN.

The solenoid operating mechanism of the ATS ensures a high-speed transfer of loads between alternate sources of power, regardless of current draw.

This ATS can handle current ranges from 30-50 Amps.

FEATURES:

- ATS Auto Transfer Switch
- Automatic & Manual Function
- Mains Power Indicator
- Generator Power Indicator
- Load Indicator
- Battery Voltage Indicator
- Failure Light
- Lockable Cabinet
- Single Phase 240V
- Dimensions: 25cm x 14cm x 32cm



GSC - P Heavy Duty Parallel Connector High Amp

Superior Quality - Unprecedented Functionality - Exceptional Value

Paralleling is connecting two inverter generators to each other via a dedicated parallel cable or kit. This allows the combining of power outputs of each generator into one outlet.

Paralleling generators is best suited when one generator does not produce enough power to run more demanding equipment such as a large air conditioner, workshop equipment, even an entire household. It can sometimes be a better choice than buying a larger single generator.

The GSC-P is used to combine two identical sized inverter generators together. The Parallel kit cannot be used with traditional non inverter generators.

- Digital Inverter Technology
- Parallel Connectivity
- 32 AMP 240 Volt IP66 Socket
- 15 AMP 240 Volt IP44 Socket
- 32 Amp Circuit Breaker
- 15 Amp Circuit Breaker





Generator Comparison Chart	INVERTER	CONVENTIONAL							
FEATURE	GSC12000i-Y	GST11000A	GST11000E	GST9500E	GST7000	GST4500	GST3500		
12-Volt DC Circuit									
15 AMP 240 Volt IP44 Socket	•			•	•	•	•		
15 AMP 240 Volt IP66 Socket		•	•						
32 AMP 240 Volt IP66 Plug Supplied	•	•	•						
32 AMP 240 Volt IP66 Socket	•	• •							
ATS Auto Transfer Switch Connection	•	•							
AVR Automatic Voltage Regulator	•	•	•	•	•	•	•		
Battery Included	•	•	•	•					
Digital Hour Usage, Hertz and Volt Meter	•	•	•	•					
Digital Inverter Technology	•								
Electric Start	•	•	•	•					
Euro V Emissions Certification	•	•	•	•	•	•	•		
Heavy Duty Copper Alternator	•	•	•	•	•	•	•		
Large Low Noise Muffler	•	•	•						
Lift Up Lid Silenced Diesel Generator									
Long Range 30 Litre Fuel Tank		•	•	•					
Long Range 34 Litre Fuel Tank	•								
Low Idle Mode	•								
Low Noise Emission	•	•	•	•	•	•	•		
Massive Air Cleaner	•								
Never Flat Wheels	•	•	•	•					
Oil Alert Light	•	•	•	•					
Oil Alert Shut Down					•	•	•		
Parallel Connectivity									
Push Button Start	•	•							
RCD Safety Switch Worksite Compliant		•	•						
Silenced Diesel									
Silenced Quiet Running									
Sine Wave Technology	•								
Telescopic Handle									
Two Wire Remote Start Connection	•	•							
USB 5 Volt Power Supply	•								



Generator Comparison Chart	CAMPING INVERTER			DIESEL					
FEATURE	GSC5000i-O	GSC3750i-Y	GSC2800i-O	GSD13000Q	GSD13000E	GSD9000Q	GSD9000E	GSD7500Q	GSD7500E
12-Volt DC Circuit				•	•	•	•	•	•
15 AMP 240 Volt IP44 Socket	•	•	•						
15 AMP 240 Volt IP66 Socket				•	•	•	•	•	•
32 AMP 240 Volt IP66 Plug Supplied				•	•	•	•	•	•
32 AMP 240 Volt IP66 Socket				•	•	•	•	•	•
ATS Auto Transfer Switch Connection				•	•	•	•	•	•
AVR Automatic Voltage Regulator	•	•	•	•	•	•	•	•	•
Battery Included	•			•	•	•	•	•	•
Digital Hour Usage, Hertz and Volt Meter	•	•	•	•	•	•	•	•	•
Digital Inverter Technology	•	•	•						
Electric Start	•			•	•	•	•	•	•
Euro V Emissions Certification	•	•	•						
Heavy Duty Copper Alternator	•	•	•	•	•	•	•	•	•
Large Low Noise Muffler	•	•	•	•		•		•	
Lift Up Lid Silenced Diesel Generator						•		•	
Long Range 30 Litre Fuel Tank									
Long Range 34 Litre Fuel Tank									
Low Idle Mode	•	•	•						
Low Noise Emission	•	•	•	•	•	•	•	•	•
Massive Air Cleaner				•	•	•	•	•	•
Never Flat Wheels	•	•	•	•		•	•	•	•
Oil Alert Light	•	•	•	•	•	•	•	•	•
Oil Alert Shut Down									
Parallel Connectivity	•	•	•						
Push Button Start	•								
RCD Safety Switch Worksite Compliant				•	•	•	•	•	•
Silenced Diesel				•		•		•	
Silenced Quiet Running	•	•	•	•		•		•	
Sine Wave Technology	•	•	•						
Telescopic Handle	•	•	•						
Two Wire Remote Start Connection				•	•	•	•	•	•
USB 5 Volt Power Supply	•	•	•						

